

SDI2USB3

3G-SDI TO USB 3.0 VIDEO CONVERTER (+ LOOP)

DEVICE CONNECTORS



- Cost-effective professional camera converter solution that is reliable as well as simple to install and connect (no driver required)
- Designed and manufactured in Canada
- TAA-compliant



OVERVIEW

INOGENI's SDI2USB3 video converter enables 3GSDI cameras to connect with computers, laptops or CODECs—without the glitches or complicated setups.

- 3GSDI professional video capture to USB 3.0
- Highly stable signal
- Active loop output connector
- Perfectly compatible with Logitech UC cameras and CODECs
 - Logitech-tested compatible cameras: Rally and Rally Bar series, MeetUp, MeetUp 2, Scribe, and consumer cameras
 - Logitech UC CODECs: Rally Bar and Rally Bar series (Appliance Mode), Roommate, for MTR and Zoom Rooms
- Compatible with Barco ClickShare Conference (CX-20, CX-30 & CX-50)
- Compatible with Zoom Rooms and Zoom Certified
- Certified Microsoft Teams Rooms:
 - Crestron's Automate™ VX is certified for Microsoft Teams Rooms with Crestron cameras and INOGENI's SDI2USB3.

WHAT'S IN THE BOX

- 1 x 1 m/3 ft. USB 3.0 cable (Type-A to Type-B)

HOW DOES IT WORK?


The SDI2USB3 professional video converter features a 3GSDI input with active loop output and supports SD and HDTV video formats. Compact in size and powered directly from a USB 3.0 port, the converter is a practical and easy-to-use USB 3.0 capture solution.

UVC-compliant, it will work with all DirectShow compatible software. The SDI2USB3 video converter supports 1080p resolution up to 60 fps.

FEATURED CONNECTORS



DEVICE INTERFACES



TECHNICAL SPECIFICATIONS

VIDEO INPUT

Connector & video resolutions	1x BNC (3GSDI input) 1x BNC (3GSDI active loop out) 3G: 1080p60/59.94/50 (Level A, B-Dual Link) HD: 1080i60/59.94/50, 1080p30/29.97/25/24/23.98 and 720p60/59.94/50/30/29.97/25/24/23.98 SD: NTSC/PAL
Jitter (alignment)	HD/SD: <0.2 UI 3 Gb/s: <0.4 UI
Cable length	150 m (492 ft.) at 1.485 Gb/s 120 m (393 ft.) at 2.970 Gb/s
Frame rates	60, 59.94, 50, 30, 29.97, 25, 24, 23.98 Hz
Color space	YCbCr, 4:2:2
Sampling rate	148.5/148.35 MHz
Emdedded audio	Ch 1&2 48kHz LPCM

VIDEO OUTPUT

Connector & video resolutions	1x BNC (3GSDI active loop out)
Color space	YCbCr 4:2:2
USB - Connector & video resolutions	1x USB 3.0 Type-B
USB - CODECs	YUY2 4:2:2 8-bit for USB 3.0 MJPEG for USB 2.0*
Notes for MJPEG for USB 2.0	* Devices having serial numbers >= SD2036XXX will support MJPEG over USB 2.0. Otherwise, it will be uncompressed video.
USB - Video scaler	Automatic hardware based
USB - Color space conversion	Automatic hardware based
USB - Sampling conversion	Automatic hardware based
USB - Frame rate conversion	Automatic hardware based

TECHNICAL SPECIFICATIONS - CONT.

COMPATIBILITY	
Barco ClickShare Conference compatibility	Compatible with Barco ClickShare Conference (CX-20, CX-30 & CX-50)
Zoom Rooms compatibility	Compatible with Zoom Rooms and Zoom Certified
Microsoft Teams compatibility	Certified Microsoft Teams Rooms: Crestron's Automate™ VX is certified for Microsoft Teams Rooms with Crestron cameras and INOGENI's SDI2USB3.
Logitech cameras and UC CODECs compatibility	Logitech-tested compatible cameras: Rally and Rally Bar series, MeetUp, MeetUp 2, Scribe, and consumer cameras Logitech UC CODECs: Rally Bar and Rally Bar series (Appliance Mode), Roommate, for MTR and Zoom Rooms
Operating system	NO driver installation necessary! Windows 7 and above (32/64-bit) macOS 10.10 and above Linux (kernel v2638)
Consumed USB tiers	1 tier The device is a simple USB composite device which include video, audio, and control interfaces. It will consume 1 tier.
Minimum host requirements	USB 2.0 port – We recommend USB 3.0 for uncompressed video 4GB RAM Intel Core i5 or equivalent Graphic card with dedicated memory
Motherboards	Compatible with all motherboards: Intel, Renesas, ASMedia, and Fresco Logic
Supported cameras	Cameras and camcorders with a SDI output
Software compatibility	UVC-compliant, it runs with all software compatible with DirectShow, AVFoundation and V4L2. Compatible with: Teams, Zoom, Webex, Google Meet, etc.

AUDIO	
Analog audio I/O	2-channel LPCM audio from SDI
Audio input connector	Ch 1&2 48kHz LPCM from SDI

PHYSICAL DETAILS	
Dimensions (W x L x H)	7.0 cm x 8.3 cm x 2.3 cm 2.76" x 3.27" x 0.90"
Power supply	Powered by USB (5V / 580mA)
Weight	130 g (0.29 lb)
Package content	1x 1 m/3 ft. USB 3.0 cable (Type-A to Type-B)
Operating temperature	0° to 45° C / 32° to 113° F
Storage temperature	-40° to 105° C / -40° to 221° F
Relative humidity	0% to 90% non-condensing

INFORMATION	
UPC code	040232250538
Origin	Canada
Warranty	5 years: Products purchased by the end-user after August 1, 2024 2 years: Products purchased by the end-user before to August 1, 2024

CERTIFICATIONS	
Certifications	FCC, CE, RoHS, IEC62368, SoV, RCM, BSMI RoHS, BSMI, CB, KC, MSIP
TAA-compliant	Yes

For technical support, contact us at support@inogeni.com

Copyright © 2025/01 INOGENI | All Rights Reserved. INOGENI name and logo are trademarks or registered trademarks of INOGENI. Use of this product is subject to the terms and conditions of the license and limited warranty in effect at the time of purchase. Product specifications can change without notice.

inogeni.com

This sales sheet is constantly being updated. Please make sure that you have the latest version by regularly visiting inogeni.com