

# CE

## **Declaration of Conformity**

For the following equipment :

Product Name: Switching Power supply

Model Designation: GST160Ax (x=12,15,20,24,36,48)

is herewith confirmed to comply with the requirements set out in the Council Directive, the following standards were applied :

### RoHS Directive (2011/65/EU)、(EU)2015/863

#### Low Voltage Directive (2014/35/EU) :

EN 62368-1:2014+A11

CB certificate No : JPTUV-100469-M2

| Electromagnetic Compatibility Directive (2014/30/EU) :<br>EMI (Electro-Magnetic Interference) |   |                     |                                       |  |  |
|---|---|---------------------|---------------------------------------|--|--|
| Conducted emission / Radia  | ated emission<br>EN 55032:2015+A1:2020<br>EN IEC 61204-3:2018 | Class B             |                                       |  |  |
| Harmonic current  | EN IEC 61000-3-2:2019+A1:2021                                 |                     |                                       |  |  |
| Voltage flicker   | EN 61000-3-3:2013+A1:2019                                     |                     |                                       |  |  |
| EMS (Electro-Magnetic Susceptibility)   |   |                     |                                       |  |  |
| EN 55035:2017+A11:2020  | EN IEC 61204-3:2018   |                     |                                       |  |  |
| ESD air   | EN 61000-4-2:2009   | Level 4             | 15KV                                  |  |  |
| ESD contact   | EN 61000-4-2:2009   | Level 4             | 8KV                                   |  |  |
| RF field susceptibility   | EN IEC 61000-4-3:2020   | Level 3             | 10V/m                                 |  |  |
| EFT bursts  | EN 61000-4-4:2012   | Level 3             | 2KV/5KHz                              |  |  |
| Surge susceptibility  | EN 61000-4-5:2014+A1:2017                                     | Level 3             | 1KV/Line-Line                         |  |  |
| Surge susceptibility  | EN 61000-4-5:2014+A1:2017                                     | Level 3             | 2KV/Line-Earth                        |  |  |
| Conducted susceptibility  | EN 61000-4-6:2014   | Level 3             | 10V                                   |  |  |
| Magnetic field immunity   | EN 61000-4-8:2010   | Level 4             | 30A/m                                 |  |  |
| Voltage dip, interruption   | EN IEC 61000-4-11:2020 >95% dip 0.5 pe                        | riods 30% dip 25 pe | eriods >95% interruptions 250 periods |  |  |

#### Note:

The power supply is considered as a component that will be operated in combination with final equipment. Since EMC performance will be affected by the complete system, the final equipment manufacturers must re-qualify EMC Directive on the complete system again.

For guidance on how to perform these EMC tests, please refer to TDF (Technical Documentation File).

#### Energy-Related Products Directive (2009/125/EC) :

Ecodesign requirements for no-load condition electric power consumption and average active efficiency of external power supplies (EU)2019/1782

This Declaration is effective from serial number SC1xxxxxx

#### Person responsible for marking this declaration :

| MEAN WELL Enterprises C  | o., Ltd.       |   |             |  |
|--|----------------|---|-------------|--|
| (Manufacturer Name)  |                |   |             |  |
| No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 24891, Taiwan |                |   |             |  |
| (Manufacturer Address)   | $\Delta$ -     |   |             |  |
| Aries Jian/ Director, Group R&D:                                 | Tries          | Alex Tsai/ Director, Product Strategy Center: |             |  |
| (Name / Position)  | (Signature)    | (Name / Position)                             | (Signature) |  |
| Taiwan   | Aug. 2nd, 2021 |   |             |  |
| (Place)  | (Date)         |   |             |  |